



US009411202B2

(12) **United States Patent**
Kaneko

(10) **Patent No.:** **US 9,411,202 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(75) Inventor: **Bunkichi Kaneko**, Niigata (JP)

(73) Assignee: **NIPPON SEIKI CO., LTD.**, Niigata (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 16 days.

(21) Appl. No.: **13/982,241**

(22) PCT Filed: **Jan. 12, 2012**

(86) PCT No.: **PCT/JP2012/050450**

§ 371 (c)(1),

(2), (4) Date: **Jul. 26, 2013**

(87) PCT Pub. No.: **WO2012/102087**

PCT Pub. Date: **Aug. 2, 2012**

(65) **Prior Publication Data**

US 2013/0314657 A1 Nov. 28, 2013

(30) **Foreign Application Priority Data**

Jan. 27, 2011 (JP) 2011-014975

(51) **Int. Cl.**

G02F 1/1345 (2006.01)

G02F 1/1333 (2006.01)

G02F 1/1343 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/1345** (2013.01); **G02F 1/133308** (2013.01); **G02F 1/13458** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC G02F 2001/133334; G02F 1/1345;
G02F 2202/22; G02F 1/133308; G02F
1/13458

USPC 349/139

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,367,923 A * 1/1983 Ishikawa 349/68

5,283,677 A * 2/1994 Sagawa et al. 349/150

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1542527 A 11/2004

CN 101470217 A 7/2009

(Continued)

OTHER PUBLICATIONS

International Search Report issued in International Application No. PCT/JP2012/050450 mailed Mar. 13, 2012.

(Continued)

Primary Examiner — Lucy Chien

(74) *Attorney, Agent, or Firm* — McDermott Will & Emery LLP

(57) **ABSTRACT**

A liquid crystal display device less influenced by static electricity comprises a liquid crystal display element which forms a display part having inner surfaces of a pair of insulating substrates provided with transparent electrodes; a circuit substrate conductively connected to the liquid crystal display element via a lead terminals; and a conductive part formed to surround the transparent electrode. The conductive part is provided on the insulating substrate so as to avoid the positions where the lead terminals are arranged. Further included are a display panel through which the display part is visible; a first earth terminal conductively connected a first conductive pattern of the conductive part and in contact with the display panel; and a second earth terminal of which is conductively connected to a seventh conductive pattern of the conductive part to a grounding part.

4 Claims, 5 Drawing Sheets

